



## CSP ADVERTISING FLAG

### General description of the product

One of the most popular advertising products in the world. Compared to other items in our offer, flags are most exposed to special weather conditions, such as strong wind or rain. It can be used both outside and inside the showroom.

### Application and use instruction

The flag in the upper part features a tunnel, used to pull/slide the flag on the upper (horizontal) mast arm. The flag clip hook should be attached to the clamp on the vertical part of the mast. Soiling the flag is a natural process of use. Flags can shreds on the edges if not disassembly during strong wind or when exposed to weather condition, which is normal occurrence.

### Product specification

Terms of use	At wind force exceeding 22 m/s remove the flag from the must, at wind force exceeding 16 m/s, bring the flag down to half of the high of the mast or bring down the whole mast
Storage conditions	Store in the original package at a temperature of 14-25°C and a relative humidity of 40-65%
Additional remarks	None
Dimensions of the product	800mm x 2000mm / 1200mm x 3500mm (upon request dimensions may be customised)
Dimensions of the graphic area	800mm x 2000mm / 1200mm x 3500mm (upon request dimensions may be customised)
Material thickness	110 g/m <sup>2</sup>

### Graphics



Photo 1

Photo 2



## CSP ADVERTISING FLAG

### Cleaning method

None

### Warranty

The warranty does not cover mechanical damages!

The warranty will only cover damages resulting from hidden manufacture or material defects, provided that product was used in line with the instruction manual and its intended purpose and was not modified by unauthorised persons. The warranty period is 3 months of the date of sale. The warranty covers the right to have the product repaired. Any and all obligations arising from the warranty shall be fulfilled within 30 working days. In order for a claim under the warranty to be accepted, the claimant must notify us of any apparent problems with the product by sending an e-mail to [office@cspautomotive.com](mailto:office@cspautomotive.com) or filling in a dedicated contact form within 7 days of the fault being detected.